



HULL

- Color - Oyster gel coat hull
- Structural lamination w/multiple layers of hand laminated knitted fiberglass and resin
- Stringers - Continuous full length foam cored hand laminated fiberglass structural stringers
- Boarding platform with SS through bolted brackets and under mounted telescopic swim ladder
- Hull Guard - UV-stabilized PVC sheer-guard with 316 SS inset
- Fasteners - All exterior fasteners 316 SS
- Bottom Paint - Ablative black antifouling INTERLUX MICRON CSC® (2 coats)
- Bilge Pumps - 7568 LPH, in three compartments w/auto/manual switches at helm
- Bonding System - common bonding zincs on transom plus rudder and shoe zincs

DECK

- Color - Oyster gel coat
- Deck - Molded textured surface in walking & work deck areas
- Deck - Raised side decks
- Drains - cockpit
- Anchor Roller Assembly
- Bow Bitt - 316 SS Samson post
- Storage - hinged lid top deck box in cockpit w/drain and latch
- Storage - deck hatch to lazarette w/sealing gasket
- Hand Rails - Deck, 2.54cm bow and stern
- Hand Rails - 2.54cm 316 SS full length hand rails over pilot house doors and each side of salon roof
- Windows - DIAMOND SEA GLAZE® Oyster powder-coated
- Doors - DIAMOND SEA GLAZE® Oyster powder-coated: two sliding pilot house entry and one aft Dutch/hatch-style entry door
- Portlights - 20.32cm 316 SS round w/screens (2)
- Cleats - 20.32cm cap rail mounted 316 SS mooring cleats (6) with chocks (2)
- Deck Fittings - 316 SS 5.08cm fuel fill, SS 3.81cm water fills (2), SS 3.81cm waste suction fitting
- Pennant Staff receiver - in bow rail
- Lazarette Vents - powder coated louvered vents

PROPULSION / ENGINE ROOM

- Engine - Single 85kW CUMMINS® QSD2.0 electric
- Marine Reduction Gear - TWIN DISC® TM485A @ 2.40:1
- Alternator - 110 amp (12V)
- Fuel Filter - RACOR® for main engine w/10 micron element
- Exhaust - 12.70cm horizontal water lift muffler, transom exit
- Propeller - HUNG SHEN® 53.34cm x 49.53cm 4-blade bronze LH, tuned to Class 1 ISO-484 pitch tolerances
- Propeller Shaft - 3.81cm SS w/PSS® drip-less shaft seal
- Seawater Strainers - bronze
- Potable Water Pump - JABSCO® SensorMax-17® constant pressure
- Sound Insulation - 3.81cm w/barrier and silver mylar finish

PROPULSION / ENGINE ROOM

- Light - engine room (2)

HEATING

- Heating System - Hydronic heat off engine w/three outlets

GALLEY

- Refrigerator, undercounter - NOVA KOOL® R2600 DC [2.4cf / 68L]
- Cook Top
- Countertop - Laminate w/teak sea rail
- Sink - stainless steel, mirror finish single bowl w/faucet
- Cabinets
- Storage - hanging locker
- Drawers - ApplePly®, full extension ball bearing tracks & sea locks with African Mahogany faces
- Outlet - 220VAC

COMPANIONWAY

- Gauges for black water
- Hanging locker

SALON

- Table - African Mahogany
- Stereo Wiring - prewired for two speaker locations from pilothouse
- Dinette, Convertible to full berth
- Lights - Overhead, 12VDC LED w/SS bezel

PILOT HOUSE

- Helm seat - fixed w/foot rest [helm side]
- Overhead Instrument Console
- Engine Control - mechanical
- Engine Monitoring - CUMMINS® analog style gauges: water temp, oil pressure, voltmeter and tachometer w/digital call out for fuel burn, oil pressure, water temp and volts
- Compass - RITCHIE® D-55 binnacle
- Windshield wipers - pantograph style, on/off (3)
- Fan - 12VDC
- Stereo Wiring - prewired from overhead console to two stereo speaker locations [aft corners of the pilot house]
- Outlet - 220VAC
- Power Port - 12VDC

FORWARD CABIN (FOC'SLE)

- V-Berth w/filler board, upholstered foam mattress and storage under
- Chain locker forward with access hatch
- Lights - Reading, 12VDC LED (2)
- Outlet - 220VAC
- Hatch - 40.64cm w/screen

HEAD COMPARTMENT

- Toilet - JABSCO® electric
- Molded one-piece head unit w/FRP sink plus faucet
- Shower - Curtain & track, textured shower sole
- Mirror - On door
- Fixtures - Toilet paper holder, towel ring & robe hook
- Door - entry w/latch
- Lights - Overhead, LED
- Outlet - 220VAC [all other CE vessels opt out in the head]



INTERIOR FINISH AND TRIM

- Upholstery - choice of colors [see option sheet/samples]
- Carpet - choice of colors [see option sheet/samples]
- Cabinet Tops - laminate w/wood searail trim
- African Mahogany trim & doors
- Overhead and bulkhead covering - vinyl w/foam backing
- Walls - vinyl

LAZARETTE

- Water Tanks (2)
- Fuel Tank
- Steering gear
- Gel coated and ventilated
- Storage space

STEERING SYSTEM

- Steering System - manual hydraulic
- Rudder and Shoe - pacified SS w/sacrificial zincs
- Rudder port bearing and shaft lip seal
- Tiller Arm - Bronze w/rudder stops
- Helm Wheel - Teak w/chrome trim ring
- Valves and fitting for autopilot hydraulic pump connection

12V DC ELECTRICAL SYSTEM

- Battery Charger - MASTERVOLT® 50 amp 3-outputs
- Battery, Start - 12V Group-31 w/box, 100 amp hours
- Batteries, House - 6V LIFELINE® deep cycle golf-cart type (2) w/boxes, 220 amp hours
- Breaker Panel 12VDC - 10-position w/LED lights
- Battery selector - BLUE SEAS® rotary switch
- Battery parallel relay
- Wire - marine grade tinned copper throughout

220V AC ELECTRICAL SYSTEM

- Shorepower, connection - 220VAC/16A
- Breaker panel - BLUE SEA® 220VAC w/LED lights
- Breaker - RCBO (1)
- Switches and outlets - VIMAR® used throughout boat

SAFETY & MOORING PACKAGE

- Fire Extinguishing System - FIREBOY® CGS-200-227 in engine room w/auto shut down
- Fire blanket
- High bilge water alarm - sensor mounted in engine room w/audible alarm at helm
- Exhaust overheat alarm - temperature sensor on main engine wet elbow w/audible alarm at helm
- Carbon Monoxide detectors in each cabin & central seating area
- Smoke Detector in each cabin & in central seating area
- Radar reflector - located in stack
- Horn - Single Electric
- Light - Anchor, LED, CE approved
- Lights - Navigation, LED, CE approved
- Mooring Lines - 1.27cm x 7.62m (2)
- Fenders - G-4 and lines (3)
- CE Certification, Class "C"

TANKAGE

- Fuel tank - 283-liter w/brass push to open valve and sight gauge

TANKAGE

- Potable Water Tank - 151-liters in two tanks w/crossover
- Gray Water Sump for shower
- Black Water Tank - 75.7-liters in keel, w/deck suction and macerator w/overboard discharge
- Tank Monitoring - Fuel, electric gauge at helm
- Tank Monitoring - Black water, in companion way
- Heater, Water - 22-liter electric/engine heat

DIMENSIONS

- Length Overall - 28' 9" / 8.76m (w/swim platform & bow roller)
- Beam - 9' 6" / 2.89m
- Draft - 3' 3" / 0.99m
- Displacement Weight - 8,500 lbs / 3,859kg
- Headroom - Pilot House 6' 2" / 1.88m
- Headroom - Salon 6' 4" / 1.93m
- Headroom - Forward Cabin 6' 0" / 1.83m

COMMISSIONING PACKAGE

- Engine Manual
- Owners Manual - w/Schematics
- Reduction Gear Manual
- Tug Operators Manual
- 10-micron fuel filter element for main engine RACOR® filter(s)
- Matched gel coat touch-up kit
- Wax Paste - Ultra Performance® 3M9030
- Assortment of screws & snap caps
- Multi-Bit Screwdriver & SS Deck Fitting Key
- Clear silicone
- Shaft Seal Collar O-Ring Kit
- Container boxes w/Lids - (2)