



HULL

- Color - Oyster gel coat hull with colored inset and waterline [standard color options]
- Structural lamination w/multiple layers of hand laminated fiberglass reinforced plastic using knitted fiberglass
- Stringers - Continuous full length foam cored hand laminated fiberglass structural stringers
- Boarding platform integrated in hull w/ telescopic swim ladder
- Hull Guards - UV-stabilized PVC-guards: anchor, hull and sheer, 316 SS inset on hull side guard
- Fasteners - All exterior fasteners 316 SS
- Bottom Paint - Ablative black antifouling INTERLUX MICRON CSC® (2 coats)
- Bilge Pumps - 7568 LPH, in three compartments w/auto/manual switches at helm
- Bonding System - common bonding zincs on transom plus rudder, shoe & thruster zincs

DECK

- Color - Oyster gel coat
- Deck - Molded textured surface in walking & work deck areas
- Deck - Raised walk-around side decks
- Door - On transom, hinged
- Scuppers - cockpit
- Anchor Roller Assembly - Polished SS
- Windlass - 12VDC LOFRANS® TIGRES® LW400AN, 1200W anchor windlass w/foot controls at bow and remote control at helm
- Bow Bitt - 316 SS Samson post
- Storage - hinged lid top deck box in cockpit w/drain
- Storage - Fender holder recess in cockpit
- Storage - Locking deck hatch to lazarette w/sealing gasket and spring-assist lifts
- Hand Rails - Deck, 3.175cm bow and stern
- Hand Rails - 3.175cm 316 SS full length hand rails over pilot house doors
- Hand Rails - 3.175cm x 76.20cm 316 SS on salon cabin top (removable starboard) and ladder on port side
- Ladder - 316 SS open rail w/wide UHMW treads from aft deck to boat deck portside
- Hand Grabs - 316 SS salon roof drains at aft salon corners
- Hand Grabs - 316 SS forward of pilot house doors
- Hand Grab - 316 SS on transom over swim ladder
- Windows - DIAMOND SEA GLAZE® Oyster powder-coated: fifteen windows (six opening w/screens)
- Doors - DIAMOND SEA GLAZE® Oyster powder-coated: two sliding pilot house entry and one aft entry
- Portlights - 20.32cm 316 SS round w/screens and drains in forward cabin trunk (6)
- Cleats - 30.48cm cap rail mounted 316 SS mooring cleats (10)
- Deck Fittings - 316 SS 5.08cm fuel fills (2), SS 3.81cm water fill, SS 3.81cm waste suction fitting
- Lighting - Aft deck overhead light
- Lighting - Boarding platform LED lights (2)
- Outlet - 220VAC [cockpit]

DECK

- Inlet - Phone/TV - dock connection
- Propane System - Regulator valve, leak sensor, shut off switch and aft deck sealed tank compartment w/overboard vent
- Pennant Staff - On bow rail
- Sea water deck washdown fore & aft
- Lazarette Vents - SS powder coated louvered vents

PROPULSION / ENGINE ROOM

- Engine - Single 283kW CUMMINS® QSB5.9 electronic
- Marine Reduction Gear - TWIN DISC® MG5061SC @ 2.43:1
- Alternator - 160 amp (12V)
- Fuel Filter - RACOR® 75/900MAX dual fuel/water separator filter for main engine
- Exhaust - 15.24cm dual stage water lift muffler transom exit for main engine
- Propeller - 71.12cm HUNG SHEN® 4-blade NiBrAl LH, tuned to class S ISO-484 pitch tolerances
- Propeller Shaft - 5.08cm SS w/PSS® drip-less shaft seal
- Seawater Strainers - bronze
- Generator Fuel Filter - RACOR® 120RMAM fuel filter / water separator for primary fuel filter
- Oil Change Pump System - plumbed to main engine, generator and transmission
- Sound Insulation - 3.81cm w/barrier and silver mylar finish
- Lights - engine room (5)
- Outlet - 220VAC

HEATING

- Furnace - Diesel ESPAR® D5LC 18,800 BTU

GALLEY

- Range - 3-burner propane stove/oven FORCE-10® 70351
- Microwave Oven - stainless steel finish
- Refrigerator - ISOTHERM® CR130PV566-LTSW, teak faced, under forward counter
- Freezer - ISOTHERM® CR090FV31ARTSW-ACDC, teak faced, under aft counter
- Countertop - CORIAN® countertop w/coved backsplash and searail, (choice of color)
- Sink - CORIAN® Cameo White, under counter mount, aft starboard corner w/single lever spray extension faucet and soap dispenser
- Cabinets - Solid teak face frames w/ teak doors and drawer faces
- Storage - Forward teak countertop cabinet unit with teak tambour rollup door and one adjustable shelf w/ plastic laminate top
- Storage - Teak corner cabinet above sink with smoke glass/teak door
- Storage - Tip-out storage in front of sink
- Storage - Four drawers aft of stove, one drawer under stove, one drawer over cabinet fwd of stove and cabinet under sink
- Drawers - ApplePly®, solid teak faces, full extension ball bearing tracks & sea locks
- Lights - Overhead, 12VDC xenon (7)
- Outlet - 220VAC



SALON

- Table - Teak mounted to fixed base
- Cabinet - Teak forward port w/rollup door
- Cabinet - Teak aft port corner w/door and teak top
- Magazine rack - Teak
- Stereo Wiring - Prewired for two speaker locations from pilothouse
- Settee - Converts to double bed w/storage under [two teak drop down doors]
- Valances - Teak
- Lights - 12VDC Xenon overhead lights (3)
- Lights - Stair LED
- Light - Reading 12VDC
- Outlet - 220VAC
- Outlet - Phone/TV, in aft port cabinet

PILOT HOUSE

- Helm seat - adjustable slider w/foot rest
- Chart table Graphite laminate top, teak faced with chart drawer
- Full width overhead instrument console w/storage
- Engine Control - electronic single lever throttle/shift
- Fuel Gauge - Integrated in SmartCraft VesselView LCD
- Engine Instrumentation - CUMMINS® SmartCraft VesselView LCD
- Bow Thruster Control - joystick
- Compass - RITCHIE® FN-203 flush mount
- Windshield wipers - pantograph style, adjustable speed, self park with washer systems (3)
- Defrost - 12VDC w/two speed fan
- Wire for speakers and power for stereo
- Lights - overhead, 12VDC red LED (2)
- Lights - overhead, 12VDC (6)
- Light - chart (red/white)
- Outlets - 220VAC
- Power Ports - 12VDC (2)
- 12VDC terminal block for electronics in overhead console
- Hatch - 41.91cm w/screen

FORWARD MASTER

- Queen-size island berth
- Mattress - hinged pillow top delux coil spring
- Mirror - full length next to entry door with teak trim
- Drawers under berth (4)
- Hull side storage cabinets w/open shelves forward
- Hull side hanging lockers w/automatic lights, w/teak tops (2)
- Lights - overhead, 12VDC (3)
- Lights - reading, 12VDC, over berth (2)
- Outlet - Phone/TV, inside starboard hanging locker
- Outlets - 220VAC, in hanging lockers
- Hatch - 55.88cm w/screen
- Chain locker forward w/access door behind headboard

GUEST CABIN

- Berth - Lower double
- Mirror - above three-drawer dresser w/teak trim

GUEST CABIN

- Hanging locker - w/automatic light, w/teak top and teak door
- Teak shelf forward on forward bulkhead
- Teak three door cabinet on forward bulkhead
- Teak three-drawer dresser aft, w/teak top
- Sliding teak entry door
- Lights - overhead, 12VDC (3)
- Lights - reading 12VDC (2)
- Outlet - 220VAC, in hanging locker

HEAD COMPARTMENT

- Toilet - TECMA® EasyFit [household size]
- Cabinet - vanity w/storage below, teak doors, CORIAN® top "Savannah"
- Sink - stainless steel w/faucet
- Shower - fiberglass w/bi-fold door
- Mirror - over sink, teak trim
- Fixtures - toilet paper holder, towel rings & bar
- Floor covering - Linoleum
- Lights - 12VDC overhead dome (2)
- Exhaust fan w/switch

INTERIOR FINISH AND TRIM

- Upholstery - choice of colors [see option sheet/samples]
- Carpet - choice of colors [see option sheet/samples]
- Teak cabinet doors and drawer faces
- Valances, Teak - salon
- Teak interior passageway doors and trim
- CORIAN® - choice of colors [see option sheet/samples]

LAZARETTE

- Macerator - Black water tank discharge pump
- Steering gear
- Completely gel coated and ventilated
- Storage space

STEERING SYSTEM

- Steering System - hydraulic
- Rudder and Shoe - SS w/ sacrificial zincs
- Rudder port bearing and shaft lip seal
- Tiller Arm - Bronze w/rudder stops
- Helm Wheel - Teak
- Valves for autopilot hydraulic pump connection
- Bow Thruster - LEWMAR® 185 TT 5.0kW 12V @ 81kgf thrust

12V DC ELECTRICAL SYSTEM

- Battery Charger - 12/50 4-stage
- Batteries, Start - 12V AGM Group-31 (2) w/boxes
- Batteries, House - 6V AGM deep cycle golf-cart type (4) w/boxes 440 amp hours
- Batteries, Thruster/Windlass - 12V AGM Group-31 (2) w/boxes
- Master house bank circuit breaker switched at DC Panel
- Battery parallel switch
- Wire - marine grade tinned copper throughout



220V AC ELECTRICAL SYSTEM

- Generator - NORTHERN LIGHTS® 5kW, 220V/50Hz w/sound shield
- Shorepower, connection - 220VAC/16A
- Shorepower, cordset - 50' 220VAC/16A
- Breaker panel - BLUE SEA® 220VAC w/LED lights
- Breaker - RCBO (1)
- Switches and outlets - VIMAR® used throughout boat

SAFETY & MOORING PACKAGE

- Fire Extinguishing System - FIREBOY® CGS-500-227 in engine room w/ auto shut down
- Fire blanket
- High bilge water alarm - Sensor mounted in engine room w/ audible alarm at helm
- Exhaust overheat alarm - Temperature sensor on main engine wet elbow
- Carbon Monoxide detectors in each cabin (2) and in central seating area (1)
- Smoke Detector in each cabin (2) and in central seating area (1)
- Radar reflector
- Horn - Dual electric
- Light - Anchor USCG approved
- Lights - Navigation USCG approved
- Mooring Lines - 1.5875mm x 63.50cm (4)
- Fenders - G-5 and lines (4)
- CE Certification

TANKAGE

- Fuel tanks - 1211-liter in two tanks w/crossover line
- Potable Water Tank- 545-liter
- Gray Water Tank - 34-liter in keel, with automatic 12V DC pump
- Black Water Tank - 121-liter in keel, w/deck suction and macerator w/overboard discharge
- Tank Monitoring - Fuel, electronic gauge at helm
- Tank Monitoring - Potable water, electric gauge and sight glasses
- Black water monitoring system
- Heater, Water - 40-liter electric/engine heat
- Fresh water pump - constant pressure

DIMENSIONS

- Length Overall w/optional Bow Pulpit - 41' 3" / 12.57m
- Length Overall - 40' 0" / 12.19m (rigged)
- Beam - 12' 11" / 3.94m
- Draft - 4' 4" / 1.32m
- Freeboard - Amidships, at pilothouse door 4' 0" / 1.22m
- Freeboard - at cockpit 3' 5" / 1.04m
- Height from - Waterline-top to stack top 10' 11" / 3.33m
- Displacement Weight - 22,600 lbs / 10,273kg
- Headroom - Salon 6' 7" / 2.01m
- Headroom - Forward Cabin 6' 7" / 2.01m
- Headroom - Pilot House 6' 6" / 1.98m

COMMISSIONING PACKAGE

- Engine Manual
- Owners Manual - w/Schematics

COMMISSIONING PACKAGE

- Reduction Gear Manual
- Tug Operators Manual
- Fuel filter element for primary RACOR® filters
- Matched gel coat touch-up kit
- Wax Paste - Ultra Performance® 3M9030
- Video - CORIAN® care and maintenance
- Assortment of screws & snap caps
- Multi-Bit Screwdriver & SS Deck Fitting Key
- Clear silicone
- Shaft Seal O-Ring Kit
- Container boxes w/Lids - (2)